

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

B63C 11/26, H04B 11/00

(11) International Publication Number:

WO 98/17526

A1

(43) International Publication Date:

30 April 1998 (30.04.98)

(21) International Application Number:

PCT/EP97/05669

(22) International Filing Date:

15 October 1997 (15.10.97)

(30) Priority Data:

MI96A002179

22 October 1996 (22.10.96)

IT

(71) Applicant (for all designated States except US): E.T.G. ELET-TRONICA DI TERLISIO GIAMPAOLO [IT/IT]; Viale R. Serra, 14, I-20148 Milano (IT).

(72) Inventor; and

- (75) Inventor/Applicant (for US only): TERLISIO, Giampaolo [IT/IT]; E.T.G. Elettronica di Terlisio Giampaolo, Viale R. Serra, 14, I-20148 Milano (IT).
- (74) Agent: TRUPIANO, Roberto; Brevetti Europa S.r.l., Piazza Bernini, 6, I-20133 Milano (IT).


(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CALL AND/OR SIGNAL TRANSMITTING AND RECEIVING DEVICE FOR SCUBA DIVERS DURING IMMERSION



(57) Abstract

Call, alarm or like device for scuba divers during immersions, made up by a substantially cylindrical hollow container (1), sealed at the opposite ends by two stoppers (2, 3) or the like, within which an ultrasound electromagnetic electronic receiving and transmitting circuit (5) is provided, with the relevant sensors for the reception (4) and transmission (5) of electro-acoustic signals, in communication with the outside of the container, as well as for the transformation of the received signals into audio-visible or vibration based warnings, said electronic circuit being fed by a cell or accumulator of a known type, enclosed within said container in such a way as to keep constantly fed the signal reception circuit on immersing and to allow the activation of the transmission circuit through a switch activated by pulling a rope or a fall ending with a knob or the like for hand-activation.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi ·	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Сатигооп		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
1212	Fatania	I D	Liberia	90	Singapore		

CALL AND/OR SIGNAL TRANSMITTING AND RECEIVING DEVICE FOR SCUBA DIVERS DURING IMMERSION

DESCRIPTION

The present invention relates to an ultrasound two-way transmission device particularly suitable for calls and for alarm and/or danger signals between scuba divers during immersions, by means of electro-acoustic signals.

As is well known to swimmers and in particular to scuba divers during immersions, it is very difficult to draw the attention of the other scuba divers and/or the other underwater companions to transmit them calls or alarm signals, when special dangerous situations happens and, besides, it is necessary to co-ordinate actions, make common directions to be taken, or other reasons; this is due to the freedom movement each scuba diver enjoys, the slowness of movements because of the equipment borne or the pure distraction or distance between the various divers.

20 At present, call signals between scuba divers are emitted by waving the arms according to movements agreed on or by particular waiving of the instruments or equipment the same scuba divers may held in the hand, or by acoustic, mechanical or hand calls of any

25 type.

Obviously, these types of signals require that the scuba diver(s) to whom the signals are directed be in condition of seeing or hearing directly the diver that gives out the call, which in the practice does not take place always, or even takes place seldom.

Object of this invention is to provide a call or alarm signal designed and structured such as to eliminate the presently used signal systems between scuba divers during immersions, and above all to eliminate the need of a direct view between the divers and to ensure the arrival of the call signal even in case of a great distance between the various scuba divers.

Another object of this invention is to provide a call device applicable also to the hydrostatic equipment of any scuba diver, structured in such a way as to ensure a very reduced overall size and weight, and also such as to be highly reliable up to a very great depth, for instance of 100 metres.

Another object is to provide a device of the aforementioned type so designed as to be easily anchorable and removable from the equipment of the scuba diver, realisable to very reduced cost and easily activable in any underwater conditions.

5

Another not last object of the invention is to provide coding means to allow a two-way signal transmission only by the concerned divers.

These and still other objects that will become more apparent thanks to the following description, achieved by a call and signal device for scuba divers during immersions and the like, which is made up, according to the present invention, by a high rigidity container, substantially a cylindrical hollow body, sealed by stoppers or the like, including in the inside an ultrasound electromagnetic electronic twoway transmission circuit with the related sensors for receiving and transmitting electro-acoustic signal, said sensors being in communication with the outside 15 of the container, as well as for the transformation and emission of suitable audio calls, and/or luminous calls and/or vibration based calls on the reception of said electro-acoustic signals, said electronic circuit being fed by a cell or an electric accumulator of a known type within said container, in such a way as to close or self-feed on the contact with water or other conductive element or conductor and such as to keep constantly fed the signal reception circuit and of their transformation and call issuing circuit, 25 also such as to allow the activation the

transmission circuit through a switch actionable by pulling a rope or a fall ending with a knob or the like for hand-activation.

More particularly, said calling device is provided, on
the external surface of the container, with a length
of peelable adhesive tape, known by the "Velcro" trade
name, suitable to allow an easy hooking, by banding
with more tape, of the container to the conventional
buoyancy equilibrator of a conventional apparatus for
scuba divers during immersions.

Besides, between said accumulator and said electronic two-way transmission circuit a code selector is located, suitable to ensure that the electro-acoustic

signals issued and received are reserved only for the

15 divers that utilise the coded device.

the conventional equipment of divers.

According to the present invention, the call device may be advantageously associated, also as an integrated part, with the mask of the diver, with the inside of a flash-light or with the inside of the decompression computer, or with the inside of the knife handle, or other suitable apparatuses that form

Further characteristics and advantages of this invention will be stressed by the following detailed description made with reference to the only attached

figure, showing a view of a preferred non limiting embodiment of the device subject matter of the invention

With reference to said only figure, the device is substantially made up by a container having a tubular shape 1 from plastic material or metal, resistant to the pressure exercised by water at a depth of at least 100 metres.

Said tubular body 1 can be sealed by two end stoppers

10 2 and 3, so as to form a water-tight sealed container.

In length 1a of container 1 an electronic circuit is included comprising an electromagnetic ultrasonic digitalised coded two-way transmission device of a known type (not shown) such as for instance the one

15 subject matter of the patent application no. MI95A 001072 in the name of the same applicant, activated through a circuit similar to the one utilised for the activation of a quick exhaust valve of the buoyancy equilibrator associated to the equipment of scuba divers during immersions.

In length 1b of the same tubular body 1 there is housed a cell or an accumulator, for instance of the alkaline tubular low voltage - substantially a 9 volt - type, which is kept constantly in contact with the

entries of said two-way transmission circuit by closing said stopper 2.

The sensor of the receiving stage 4 and the sensor of the transmitting stage 5 are located in contact with water (either sea- lake- or river water), so as to allow the transmission and reception of ultrasound signals by exploiting water conductivity.

The received signals are transformed into luminous calls, audio-calls or vibration based calls having an intensity sufficient to be easily heard by the diver provided with the calling device, also at a long

distance from the emitting apparatus.

In stopper 3 a magnetic switch is associated to the transmission circuit 5, which can be activated from the outside of the tubular body by pulling a rope 6, either rigid or flexible, passing through the stopper and ending by a grasp-knob 7 or the like.

Besides, in order to allow the exchange of signals at a distance only between two or more divers, in housing

20 1b of the tubular body 1 an impulse selector (not shown) is provided, for the coding of said signals.

Lastly, on the external surface of tubular body 1, there is stably wound, according to a preferred embodiment, at least a length of an adhesive indented

25 tape 8 known by the "Velcro" trade name, which allows

to hook the calling device to the conventional buoyancy equilibrator of diver equipment, also provided with lengths of Velcro tape.

Obviously, instead of Velcro tapes for quickly hooking
and unhooking the calling device of the equilibrator,
hooks or other anchoring means may be provided that
can perform the same function.

In practice, the above described device remains activated throughout the immersion time and, more particularly, there remains activated uninterruptedly only the receiving circuit that receives the signal and provides to the emission of an acoustic signal and/or luminous signal or even of a vibration based signal which is perceived by the diver, while the transmitting circuit is activated by the diver only if the situation should so require.

Actually, if two or more divers, all of them provided with the same calling device, are underwater at the same time, one (or more than one) of them closes the transmission circuit by pulling the knob 7 of his device, sending in this way an electro-acoustic signal to the other divers who, on receiving the call on their device, can pay attention or go towards the other ones, or towards the diver who has called, if only two divers are underwater.

In practice, the above described device may be utilised to perform manoeuvres or other tasks if the divers, before the immersion, have agreed on performing some manoeuvres according to a special code, such as for instance the following one: the transmission of one only signal means that a given manoeuvre should be performed by all divers; the transmission of two signals means that another type of previously agreed manoeuvre should be performed, and so on.

In these cases, all the manoeuvres agreed on can be carried out with no need for divers to look at each other or to approach to each other.

To sum up, the above description made with reference

15 to the attached figure stresses the great practical importance of the present invention, which allows to solve in a simple, quick manner and in safe conditions, any problem of co-ordination between scuba divers during immersions.

It is lastly obvious that many variants and modifications, equivalent from the structural and functional point of view, may be introduced in the invention as described according to a preferred embodiment, which variants and modifications fall within the protection scope of the invention.

CLAIMS

1. A call, alarm and/or signal transmission electronic device for scuba divers during immersions and the like, characterised in that it is made up by a container, substantially a hollow cylindrical body (1), water-tight sealed, comprising in the inside an electromagnetic electronic ultrasound two-way transmission circuit with the related sensors (4, 5) for the reception and transmission of the electro-10 acoustic signals, said sensors being in communication with the outside of the container, as well as for the transformation and emission of suitable audio signals and/or luminous signals and/or vibration based signals on receiving said electro-acoustic signals, said 15 electronic circuit being fed by a cell or an accumulator of a known type, included in container (1), in such a way as to close or self-feed on the contact with water or other conductive element or conductor, and as to keep constantly fed the 20 circuit (4) that receives the signals and transforms emits them, and also such as to allow the activation of the transmission circuit (5) through a switch activated by pulling a rope or a fall (6) ending by a knob (7) or the like for hand-activation.

- 2. The electronic device according to claim 1, characterised in that a coding selector is located between said electronic circuit and said electric accumulator, suitable to ensure that the signals emitted or received are used only by the divers who are provided with said calling device.
 - 3. The electronic device according to claim 1, characterised in that the calling device is advantageously associated, also as an integrating part, with the mask of the diver, or with the inside
- of a flash-light, or with the inside of a flash-light, or with the inside of the decompression computer, or with the knife handle or any other apparatus that make parts of the conventional equipment of all scuba divers.
- 15 4. The electronic device according to claim 1, characterised in that to the container 1 a length of adhesive tape (8) is anchored, of the type peelable and re-attachable several times, which is the means for quickly hooking and unhooking the device to the 20 buoyancy equilibrator that makes part of the equipment of scuba divers.
 - 5. The electronic device according to claim 1, characterised in that it is fed by a low voltage substantially 9 volt accumulator or electric cell.

6. The electronic calling device according to the preceding claims, characterised in that it is realised for the purposes and tasks as above specified, according to what has been described and illustrated.

5

10

15

20




fig.1

INTERNATIONAL SEARCH REPORT

Intel onal Application No PCT/EP 97/05669

A. CLASS	B63C11/26 H04B11/00							
	According to International Patent Classification(IPC) or to both national classification and IPC							
	S SEARCHED locumentation searched (classification system followed by classific	antion cumbata)	· · · · · · · · · · · · · · · · · · ·					
IPC 6	B63C H04B	cation sympols)						
Documenta	ation searched other than minimumdocumentation to the extent th	at such documents are included in the fields se	arched					
Electronic	data base consulted during the international search (name of data	base and, where practical, search terms used)					
		•						
	ENTS CONSIDERED TO BE RELEVANT							
Category *	Citation of document, with indication, where appropriate, of the	relevant passages	Relevant to claim No.					
Υ	US 5 523 982 A (DALE) 4 June 19 see the whole document	96	1-6					
Υ	GB 2 108 666 A (BARNES MANAGEME DEVELOPMENT SERVICES LTD) 18 Ma see page 1, line 100 - line 123	y 1983	1-6					
A .	US 3 469 231 A (GEILING ET AL) September 1969 see the whole document	23	1-6					
		·	. :					
		·						
	*.							
Furth	er documents are listed in the continuation of box C.	Patent family members are listed in	annex.					
° Special cat	egories of cited documents :	"T" later document published after the inter-						
"A" docume conside	nt defining the general state of the art which is not ered to be of particular relevance	or priority date and not in conflict with the cited to understand the principle or the invention						
"E" earlier de filling da	ocument but published on or after the international	"X" document of particular relevance; the ci cannot be considered novel or cannot						
which is	nt which may throw doubts on priority claim(s) or s cited to establish the publication date of another	involve an inventive step when the doc "Y" document of particular relevance; the cl	ument is taken alone					
"O" docume	or other special reason (as specified) nt referring to an oral disclosure, use, exhibition or	cannot be considered to Involve an inv document is combined with one or mo	entive step when the re other such docu-					
	leans nt published prior to the international filing date but an the priority date claimed	ments, such combination being obvious in the art. "&" document member of the same patent for						
	ctual completion of theinternational search	"&" document member of the same patent for Date of mailing of the international seam						
11	February 1998	02/03/1998	·					
Name and m	ailing address of the ISA	- Authorized officer						
	European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	DE SENA, A						
	(),							

INTERNATIONAL SEARCH REPORT

Intel onal Application No PCT/EP 97/05669

			01, 21 37, 00003	
A. CLASS	B63C11/26 H04B11/00			
According t	to International Patent Classification(IPC) or to both national classif	ication and IPC	•	
ľ	SEARCHED			
IPC 6	ocumentation searched (classification system followed by classifica B63C H04B			
	tion searched other than minimum documentation to the extent that			
Electronic	lata base consulted during the international search (name of data b	ase and, where practical, sea	rch terms used)	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the re	elevant passages	Relevant to claim No).
Υ	US 5 523 982 A (DALE) 4 June 199 see the whole document	1-6		
Υ	GB 2 108 666 A (BARNES MANAGEMEN DEVELOPMENT SERVICES LTD) 18 May see page 1, line 100 - line 123;	1983	1-6	
Α	US 3 469 231 A (GEILING ET AL) 2 September 1969 see the whole document	3	1-6	
χ.				
Furthe	er documents are listed in the continuation of box C.	X Patent family memb	pers are listed in annex.	
* Special cate	egories of cited documents:	"T" later document published	after the international filing date	
conside	nt defining the general state of the art which is not red to be of particular relevance	or priority date and not	in conflict with the application but principle or theory underlying the	l
filing da "L" documen	t which may throw doubts on priority claim(s) or	cannot be considered n	elevance; the claimed invention ovel or cannot be considered to p when the document is taken alone	
which is citation	cited to establish the publicationdate of another or other special reason (as specified) It referding to an oral disclosure, use, exhibition or	"Y" document of particular re cannot be considered to	blevance; the claimed invention Involve an inventive step when the with one or more other such docu-	
other m P" documen	eans t published prior to the international filling date but n the priority date claimed	ments, such combinatio in the art.	n being obvious to a person skilled	
	stual completion of theinternational search	"&" document member of the Date of mailing of the Inte		\dashv
11	February 1998	02/03/1998		
Vame and ma	illing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	Authorized officer	,	
	NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fax: (+31-70) 340-3016	DE SENA, A	•	

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
FADED TEXT OR DRAWING
BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
OTHER.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.